

Technical data sheet

FV130.2

Execution for: Brunei Darussalam

Utensil washer

Programme start button: right

Working height: 845 mm

3-phase current: 3N PE 400V 50Hz

Fresh water line: Soft cold water 0-3 °dH



© MEIKO 2016
Sample illustration

Technical data

Rack capacity/h (theoretical)	30 / 15 / 10 racks/h
Programme cycle time	120 / 240 / 360 s
Rack dimension	850 x 700 mm
Entry height	740 mm
Dimensions (W x H x D)	1030 x 1785 x 895 mm
Electrical feeding cable	3-phase current 3N PE 400V 50Hz* Total connected load: 14,7 kW max. rated current: 25,4 A
Protection class of the machine	IP X5
Equipment	MIKE 2 control Infrared interface for wireless communication Leakage detector Soft start Wash arm drive Boiler safety device Drain pump Automatic self-cleaning when tank is drained Aqua-Stop system Back wall cladding
Fresh water line	Air gap 'AA' in accordance with EN 1717 with booster pump
Fresh water supply	Minimum flow pressure 60 kPa / 0,6 bar in front of solenoid valve Maximum pressure: 500 kPa / 5,0 bar Max. supply water temperature 60 °C
Flow rate	5,0 l/min
Final rinse water quantity	5,8 liters/cycle

Technical data sheet

Boiler	Contents: 18,0 l Heater: 12,00 kW Temperature: 83 °C Tank / boiler locked
Wash tank	Filling: 85,0 l Heater: 6,00 kW Temperature: 60 °C
Wash pump	Performance: 2,20 kW
Dosing of rinse aid	Hose pump (24 V) with time control and suction lance
Material	Cladding: 1.4301 Wash tank: 1.4301 Boiler: 1.4404
Heat emission	for 15 programme cycles/h total: 4,5 kW perceptible: 3,0 kW latent: 1,5 kW
Ventilation flow rate	1150 m ³ /h
Steam emission	2,1 kg/h
Emission sound pressure level at the workplace (LpA)	69 dB
Net weight	270,0 kg

*Note:

Electrical equipment suitable for supply voltage:
3N PE 400 V 50 HZ (3N PE 380-415 V 50 Hz)