## Technical data sheet



## M-iClean HXL

Type: M2

Execution for: Brunei Darussalam

**Dishwashing machine** 

Working direction: right - left Working height: 850 mm

3-phase current: 3N PE 400V 50Hz Fresh water line: Soft cold water 0-3 °dH



Sample illustration

© MEIKO 2018

## **Technical data**

(with handles)
nunication
drained
717 with booster pump
bar in front of solenoid valve
r

M-iClean page 1 / 2 OM000022037.2.5 M-iPlan 11/08/2020





Boiler	Contents: 18,0 I
	Heater: 18,00 kW
	Temperature: 83 °C
	Tank / boiler locked
Wash tank	Filling: 54,0 I
	Heater: 8,00 kW
	Temperature: 60 °C
Wash pump	Performance: 2 x 0,75 kW
Dosing of rinse aid	Hose pump (24 V) with time control
	and suction lance
Detergent dosage	Hose pump (24 V) with time control
	and suction lance
Material	Cladding: 1.4301
	Wash tank: 1.4301
	Boiler: 1.4571
Heat emission	for 25 programme cycles/h
	total: 5,4 kW
	perceptible: 3,6 kW
	latent: 1,8 kW
	1360 m³/h
Steam emission	2,6 kg/h
Emission sound pressure level at the workplace (LpA)	67 dB
Net / gross weight	210,0 kg / 245,0 kg (standard packaging)
Packaging dimensions (W x H x D)	1000 x 1750 x 1350 mm (standard packaging)

## \*Note:

Electrical equipment suitable for supply voltage: 3N PE 400 V 50 HZ (3N PE 380-415 V 50 Hz)

M-iClean page 2 / 2 OM000022037.2.5 M-iPlan 11/08/2020